

Technical data

General	Lubrication and filling unit
Dimension	Size: 420 x 325 x 180 mm Weight: 13 kg
Power supply	Power: 110 V AC 50Hz-60Hz or 230-240 V AC 50-60 Hz
Maximum Output Pressure	300 BAR/4351 PSI.
Output Volume	Up to 1600 ml/min Up to 54,1 oz/min
Operation	Semi automatic
Controller	Remote controller Touch Display Hove Smart Lube
Accuracy	1%



Datasheet HOVE ONE v1

Hove ONE v1

Solid and stable lubrication unit with high accuracy

For direct lubrication of bearings and refilling of lubricants in central lubrication systems – especially wind turbine.

Optional features:

Ground failure tester

Circuit board that in case of missing or weak ground connection disables the Pump. Pump will not be able to work until ground connection is established.

Inlet system for low viscosity media

Adaptor for Cartridge connection making it possible to handle low viscosity lubricants without spillage. Cartridge adaptor is equipped with an internal check valve which keeps the lubricant inside the canister until the adaptor is fitted on the pump.

Pressureless Coupling

Function making it possible to disconnect hose with system under pressure.

By pressing down the coupling, the system will be de-pressured by guiding the pressure to the flush pipe.

Advantages of Hove One v1 pump:

- ✓ It's all packed in a suitcase
- ✓ High pressure and flow lets you get the job done Quick and easy
- ✓ Can be used for any kind of lubricant
- ✓ Dispenses correct volume of lubricant as required by supplier of component.
- ✓ Downtime reduced during maintenance
- ✓ Lubrication pressure up to 250 BAR
- ✓ Less contamination risk – fully closed circuit, from cartridge to lubrication point.

