

## Technical data

General Lubrication and filling unit

Dimension Size: 365 x 300 x 170 mm  
Weight: 9 kg

Power supply 110 - 115 VAC/ 50-60Hz  
or  
200-240 VAC/ 50-60 Hz

Maximum Output Pressure 250 BAR/3625 PSI.

Output Volume 30-600 ml/min  
1-21 oz/min

Operation Semi automatic

Controller Remote Controller  
Touch Display  
Hove Smart Lube

Accuracy +/- 1%



# Datasheet

## HOVE EASY GREASE

### v4

# Hove Easy Grease v4

## Lubrication unit with high accuracy

For direct lubrication of bearings and refilling of lubricants in central lubrication systems – especially wind turbine.

## Optional features:

### Inlet system for low viscosity media

Adaptor for Cartridge connection making it possible to handle low viscosity lubricants without spillage. Cartridge adaptor is equipped with an internal check valve which keeps the lubricant inside the canister until the adaptor is fitted on the pump.

### Pressureless Coupling

Function making it possible to disconnect hose with system under pressure.

By pressing down the coupling, the system will be de-pressured by guiding the pressure to the flush pipe.

## Advantages of Hove Easy Grease pump:

- ✓ It's all packed in a suitcase
- ✓ High pressure and flow lets you get the job done quick and easy
- ✓ Ground failure tester
- ✓ Can be used for any kind of lubricant
- ✓ Dispenses correct amount of lubricant as required by supplier of component.
- ✓ Downtime reduced during maintenance
- ✓ Lubrication pressure up to 250 BAR
- ✓ Can be used with Hove Smart Lube\*
- ✓ Less contamination risk – fully closed circuit, from cartridge to lubrication point.



\*Read more: <https://hove-as.com/solutions/smart-lube/>