

## Technical data

General	Lubrication and filling unit
Dimension	Size: 365 x 300 x 170 mm Weight: 12,5 kg
Power supply	110-115 VAC/50-60Hz or 200-240 VAC/ 50-60 Hz
Maximum Output Pressure	300 BAR/4351 PSI.
Output Volume	68-1500 ml/min 2,3 - 50,73 oz/min
Operation	Semi automatic
Controller	Remote controller Touch Display Hove Smart Lube
Accuracy	+/- 1%



# Datasheet Hove ONE

# Hove ONE

## Lubrication unit with high accuracy and high flow

For direct lubrication of bearings and refilling of lubricants in central lubrication systems – especially wind turbine.

### Optional features:

#### Inlet system for low viscosity media

Adaptor for cartridge connection making it possible to handle low viscosity lubricants without spillage. Cartridge adaptor is equipped with an internal check valve which keeps the lubricant inside the cartridge until the adaptor is fitted on the pump.

#### Pressureless Coupling

Function making it possible to disconnect hose with system under pressure.

By pressing down the coupling, the system will be de-pressured by guiding the pressure to the flush pipe.

### Advantages of Hove One pump:

- ✓ It's all packed in a suitcase
- ✓ Ground failure tester
- ✓ High pressure and flow lets you get the job done quick and easy
- ✓ Can be used for any kind of lubricant
- ✓ Dispenses correct amount of lubricant
- ✓ Downtime reduced during maintenance
- ✓ Lubrication pressure up to 300 BAR
- ✓ Can be used with Hove Smart Lube\*
- ✓ Less contamination risk – fully closed circuit, from cartridge to lubrication point



\*Read more: <https://hove-as.com/solutions/smart-lube/>